



6012 C

- Double PU Outsole
- Composite Safety Toe
- SoleGard™
- Water Resistant



Upper Material

Vamp	Leather Loc Brown S-2 1.8-2.0 mm
Mudguard	Leather Loc Brown S-2 1.8-2.0 mm
Quarter	Leather Loc Brown S-2 1.8-2.0 mm
Lacing Eyestay	Leather Loc Brown S-2 1.8-2.0 mm
Tongue Patch Top	Leather Loc Brown S-2 1.8-2.0 mm
Toe bumper	PU Coated Leather Black 1.8-2.0mm
Heel bumper	PU Coated Leather Black 1.8-2.0mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

Lining

Vamp Lining	Grey polyester
Tongue Lining	DryMax™ goremesh polyester
Collar Lining	DryMax™ goremesh polyester

Standard Compliance	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Piping	12mm Black/Silver reflective
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Gray With TPU Red Insert
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

-  Lightweight composite toe protection
-  Enhanced shock absorption for all day comfort
-  Metal free nail-proof midsole
-  PU Insole improves heel cushioning
-  Water resistant upper keeps feet dry

